

## 5-Point Ligature Resistant Door Latch Set–Mortise

#DH425

### Specification

- ANSI Grade 1 heavy duty mortise lock with 5-point ligature resistant arch trim
- Backset 2-3/4"
- Door thickness: 1-3/4", other upon request
- Stainless steel arch trim
- Stainless steel latch bolt, split, anti-friction, 3/4" throw
- Stainless steel dead bolt with anti-saw pins, 1" projection
- Stainless steel ADA thumb turn standard
- Stainless steel ANSI strike
- Tamper resistant stainless steel mounting screws
- Handed, specify handing
- Core options:
  - Schlage® "C" keyway, brass 6-pin cylinder standard
  - SFIC with or less core available, 6- or 7-pin core
  - Schlage® LFIC less core available
  - Corbin® LFIC less core available
  - High security cylinder available, Townsteel "L" keyway, 6-pin
  - High security SFIC core available, Townsteel "L" keyway, 7-pin
- KD, KA, MK, GMK, GGK and construction keying available
- Available functions: F-01, 02, 04, 05, 07, 13, 22, 26, visit [besafepro.com](http://besafepro.com) for more available functions
- Available finish: US32D
- Patent pending design
- 10-year Manufacturer's Limited Warranty



### Code Compliance

- ANSI/BHMA A156.13-2005 Grade 1 certified
- UL 10C Listed 3-Hour Fire Rating
- Meets requirements of The Americans with Disabilities Act
- Meets requirements of the Buy American Act

### Important Note

If any of our keyed locks are used less cylinder, whether IC or standard, and another manufacturer's cylinder is used in place of the original manufacturer's cylinder, we request that a sample of that product be provided in advance for testing.