



BEHAVIORAL SAFETY

INNOVATION NEVER RESTS

LIGATURE RESISTANT TOILET and FLUSH VALVE COVER

#LT700

Our ligature resistant solid surface LT700 Toilet and Flush Valve Cover includes unique features that make it ideal for new and existing patient bathrooms or public facilities in behavioral settings that necessitate ligature resistant fixtures. The LT700 is particularly suited for existing locations with fixed plumbing drainage.

The patented design limits the potential ligature attachment that other commercially available toilets and flush covers might have. Specifically, this unit eliminates any space between the toilet and the back wall found in floor mount toilets, and thereby removes the ligature risk associated with typical facility toilets. The rear cover is adjustable to accommodate existing toilet installations at different floor rough-ins between 9.25" and 13" centerline from the back wall. This feature prevents having to demo an existing floor rough-in to install the toilet, which is especially helpful in facilities with concrete flooring.

The LT700 also offers a safe solution for managing access to plumbing and for easy maintenance. The removable top of the flush valve cover allows full access to the plumbing valve for adjustment/maintenance. Because of interaction between the toilet and cover, the flush valve is always contained within the flush valve cover. Flange bolts are accessible through holes in the side of the toilet and covers are provided to secure access to the bolts.

The cover is supported by an aluminum frame screwed to the wall behind the toilet. The cover frame is a welded assembly and is mounted to the wall with stainless-steel screws and screw-in wall fasteners.

A stainless steel hardware package is provided with all screws and mounting fasteners to assemble the cover and attach the frame to the wall.

Behavioral Safety's products are thoughtfully designed and engineered in accordance with the highest quality materials and performance standards for the behavioral industry.

Specifications

- Ligature resistant design.
- Engineering grade, impact-resistant heavy gage PVC flush valve cover with removable top for easy access to plumbing.
- Custom "European" solid surface body /stainless steel bowl hybrid design toilet with fully enclosed trap.
- Rough-in from 9.25" to 13" on center (as measured from the wall) for different existing rough-in applications.
- Aluminum frame and mounting hardware secures the flush cover to the wall.
- Includes mounting hardware.
- Installs in either new or existing buildings.
- Designed to use Sloan 9603 flush valve and Sloan HY 108A flush actuator. **(not included)**
- Shipping weight 110 lbs.

