

## LIGATURE RESISTANT SHOWER PANEL

#SV725

This recessed mounted shower panel reduces ligature risk normally associated with standard systems. The product features a ligature resistant shower valve and shower head. The back panel is easily mounted through multiple side and rear mounting holes, accepting fasteners appropriate for the structure behind the unit. Designed to fit existing 4" cavities, and composed of stainless steel with exposed surfaces in a powder coated white finish. All corners are welded and ground for secure mounting. Overall dimensions of panel are 8"W x 42"H x 3-3/4"D.

### Specifications

- Cabinet materials are Type 304 stainless steel
- All exposed finish surfaces are powder coated
- Front panel anchored to mounting frame at 6 points
- Front panel secured with tamper resistant stainless steel screws
- Front panel includes flanged edge to provide flush mounting
- Ligature resistant chrome plated shower head with adjustable spray angle
- Ligature resistant chrome plated shower valve with pressure balance technology
- Valve is accessible from the front for ease of maintenance
- Mounting frame has multiple location holes built in for ease of mounting (mounting screws not included)
- Water can be supplied vertically from top or horizontal from behind the wall unit
- Overall product dimensions allow for ADA compliance
- Shipping weight 30 lbs.

### Certifications

- ADA Compliant
- This product is tested to meet:
  - UPC
  - CUPC
  - ASME A112.18.1-2012 /CSA B125.1-12
  - ASSE 1016

### Rough In

